



MK5045

Schottky Bypass Diode Module

6AE(© * ñD ¼ ±1Ñ Q ‡

Features/ × ñ(©&é

" +LJK IUHTXHQFQ ÑŠ HEDWLRQ
" /RZ IRUZDUG YR'QWLDJH GURS
" +LJK SXULW\ KXUK WŠRŠSHUDW SVXODWLRQ
HQKDQFHG PHFKDQDQDOPRWWMXUW KHVLVWDQ
Q4ß Ö ÄQ\$Y)ß"W1>ð Èjàj Ö ¼Lb%ž W -
"ORQJ WHUPKTUOH QLVDELOLW\

Typical Applications/ " » Ä+X

3KRWRYROWDLFHVRQDQ FHFQVSWRWUHFWLILH
y?ZLc7-+e"• Ö6AE(© * ñ#q~

Mechanical Data/ × ñ ò

Package/ 1>ð: *) 6
"OROGLQJ FRPSRXQG PHHWD/PDELOLW\
UDW\1Q È1V8 8/ 9 'óW1y4x
"Terminals/ E7J€É: 7LQ SODWHG OHDGV VROGHUDE
- 67' DQG -(6' K%pKQE4i È':W1V
8 - 67' -(6' %7ð
"Polarity/ ±W: \$V PDUNH1V'

Maximum Ratings 7D 8QOHVV RWKHUÄLVWNÉHF&ŠYHG D L" MŽ 9Êy

PARAMETER ð	SYMBOL 1V'	UNIT ... }	MK5045
----------------	---------------	---------------	--------

'HYLFH PDUNLQJ FRGH
× ñ »'

0.

--	--	--	--

&XUUHQW 6TXDUHG 7LPH # PV"W PV 7M
!" A#Š#¼ •, +e •#q Éé & •L\$8° €V `€VQ0\$YS p €, ,

Å7

	7M		a
--	----	--	---

127(Ö 0HHWV WKH UHTXLUHPHQWV RI ,(&UPDO(ÖHVHMSDVV GLRGH WKH
Ö Ä Å% Cã, (& (GñD ¼ ±1Ñ' W7-?±"r

Electrical Characteristics Ä7D 8QOHVV RWKHUÄLVWNÉHF&ŠYHG D L" MŽ 9?ð È

	1V'	UNIT ... }	TEST CONDITIONS #(B ' &	MK5045
--	-----	---------------	----------------------------	--------

0D[LPXP LQVWDQWDQHRXV IRUZDUG YROWDJH GURS SHU GLR,QH \$
0W!" A-Ü & »L} 9)0 !" A0 W+e#q \$



MK5045

Thermal Characteristics 7D 8 Q O H V V R W K H U Å L ' V k) 3 5 H 0 7 D L H G L " M Ž 9 ? 0 Ê

PARAMETER ð	SYMBOL 1V'	UNIT ... }	MK5045
----------------	---------------	---------------	--------

7 K H U P D O 5 H Å / L V W D Q F H

MK5045



Disclaimer
>CS

7KH LQIRUPDWLRQ SURFHVW LQ WKLV LQIRUPDWLRQ HQHUJLHV (KHFORQJLQ /WG IHU